Description 5.200 acre parcel

Being part of the southwest quarter of Section 15, Walnut Creek Township, T-9 N, R-4 W, Holmes County, Ohio.

Described as follows:

Commencing at a stone found marking the southwest corner of the southwest quarter of Section 15, thence N 03 degrees 06' 24" E 1549.25 feet along the section line to a point in the center of T.R. 406, thence S 86 degrees 46' 41" E 321.96 feet along the centerline of T.R. 406 to a point the TRUE POINT OF BEGINNING, witnessed by an iron pin set N 41 degrees 22' 08" E 34.05 feet.

thence with the following ELEVEN (11) COURSES:

- 1) N 04 degrees 36' 29" E 516.20 feet to an iron pin set;
- S 82 degrees 17' 42" E 276.04 feet to an iron pin set;
- 3) N 09 degrees 03' 50" E 94.62 feet to an iron pin set;
- 4) S 84 degrees 36' 02" E 56.51 feet to an iron pin set;
- 5) S 06 degrees 31' 02" W 69.65 feet to an iron pin set;
- 6) S 80 degrees 44' 04" E 51.97 feet to an iron pin set;
- S 04 degrees 55' 24" W 103.29 feet to an iron pin set;
- 8) S 03 degrees 52' 28" E 264.34 feet to a 5/8 inch rebar found;
- 9) S 09 degrees 01' 35" W 322.70 feet along Andrew A. Yoder and Barbara Ann Yoder's (O.R. 173 page 2732) west line to a point in the center of T.R. 406, witnessed by a 5/8 inch rebar found N 09 degrees 01' 35" E 34.86 feet;
- 10) N 37 degrees 53' 29" W 232.48 feet along the centerline of T.R. 406 to a 5/8 inch rebar found;
- 11) N 86 degrees 46' 41" W 245.54 feet along the centerline of T.R. 406 to the TRUE POINT OF BEGINNING.


This parcel contains 5.200 acres, but subject to all highways and easements of record.

All iron pins set are 5/8 inch rebars with a plastic identification cap marked "Baker 6938". Basis of bearings from Plat vol. 19 page 123.

4697 , page_ See Holmes County Plat Book_ This survey made and description prepared by Donald C. Baker, P.S. 6938. December 22, 2021

of cal

P.S. 6938



Parcel Number: 2600996012