

Stone at NW corner NE 1/4  
of NW 1/4 of S 7 T 8 N R 7 W  
S 89° 39' 36" E 479.11'

I. Pin 77.29' I. Pin S 89° 39' 36" E 2176.39' to Stone at NE corner of NW 1/4  
of NE 1/4 S 7 T 8 N R 7 W

S 26° 7' 20" E 124.40'

I. Pin

S 54° 59' 47" E 294.63'

Lucille and Donald Lowe

"A"

Parcels A & B are part of  
Vol. 170 Pg. 506

N 8° 25' 43" W 284.02'

I. Pin N 53° 35' 47" W 255.96'  
E TR 297' 66' R/W

194.60'

S 16° 32' 40" E 223.54'

I. Pin

Gravel Pit

76.46'

M 23° 29' 23" W 219.39'

I. Pin

42.78'

25.03'

N 52° 18' 26" W

25.05'

S 55° 32' 17" E 261.98'

I. Pin

"B"

Arc = 264.84'

R = 195.04' T = 157.40'

D = 29° 22' 37"

R & TR 297'

95.54'

S 49° 53' 3" W

I. Pin

Parcel A	Parcel B
2.29 Ac.	1.09 Ac.
.34 R/W	.30 R/W
1.95 Ac. Net	0.79 Ac. Net

Scale: 1" = 100'

I certify this correct to the  
best of my knowledge and belief.  
Robert L. Kasner P.S. 5193

INDEXED 103653

REC'D December 20, 1974  
AT 4:28 O'CLOCK P.M.  
RECORDED: Dec. 23, 1974  
HOLMES CO. PLAT VOL. 6 PG. 48  
FEE: \$ 3.74  
Richard Brown RECORDER  
(12.2)



MAP OFFICE COPY

PLAT OF A SURVEY FOR  
LUCILLE & DON LOWE (Grantor)  
S 7 T 8 N R 7 W of Killbuck  
Twp., Holmes Co., Ohio