

Address: 5434 TR 377, Millersburg, OH 44654

**Phone:** 330.231.0497

## Description: 2.058 Acres

Being part of the southeast quarter of section 1, Mechanic Township, T-8 N, R-7 W, Holmes County, Ohio, also known as part of the lands conveyed to John S. Mullet in Deed Vol. 224 Page 350, (PPN 1302308000) and the lands of David M. Mullet, trustee in O.R. Vol. 262 Page 2291, (PPN 1302309000), and part of the lands of Sand Run Company in Deed Vol. 257 Page 264, (PPN 1302311000).

Described as follows:

Commencing at a point marking the southeast corner of the southeast quarter of section 1 in State Route 83 witnessed by a 5/8 inch rebar found N 00 degrees 58'21" E a distance of 66.93 feet being the TRUE PLACE OF BEGINNING;

Thence with the following SIX (6) COURSES:

- 1. N 89 degrees19'33" W a distance of 345.04 feet along the section line to a point in said road;
- 2. N 00 degrees24'12" E a distance of 273.09 feet through the lands of said David M. Mullet, trustee and said Sand Run Company to an iron pin set passing over an iron pin set at a distance of 41.74 feet;
- **3. S 84 degrees17'18'' E a distance of 103.06 feet** through the lands of said Sand Run Company to a 5/8 inch rebar found;
- 4. S 83 degrees24'43" E a distance of 82.80 feet through the lands of said John S. Mullet to an iron pin set;
- 5. S 84 degrees05'53" E a distance of 168.83 feet through the lands of said John S. Mullet to an iron pin set on the section line;
- 6. S 02 degrees18'00" W a distance of 240.22 feet along the section line to the TRUE PLACE OF BEGINNING.

1 of 3

This parcel contains 2.058 acres, but subject to all highways, easements, and restrictions of record.

Also, subject to a 12 foot secondary easement for the purpose of ingress and egress described as follows;

Being part of the southeast quarter of section 1, Mechanic Township, T-8 N, R-7 W, Holmes County, Ohio, also known as part of the lands conveyed to David M. Mullet, trustee in O.R. Vol. 262 Page 2291, (PPN 1302309000) and part of the lands of John S. Mullet in Deed Vol. 224 Page 350, (PPN 1302308000).

Further described as follows:

Commencing at a point marking the southeast corner of the southeast quarter of section 1 in State Route 83 witnessed by a 5/8 inch rebar found N 00 degrees 58'21" E a distance of 66.93 feet, thence N 02 degrees 18'00" E a distance of 240.22 feet along the section line to an iron pin set, thence N 84 degrees 05'53" W a distance of 168.83 feet through the lands of said John S. Mullet to an iron pin set, thence N 83 degrees 24'43" W a distance of 16.24 feet through the lands of said John S. Mullet Corner pin set, the State St

Thence with the following FIVE (5) COURSES along the centerline of said 12 foot easement;

- 1. S 39 degrees15'27" W a distance of 36.65 feet through the lands of said John S. Mullet, and David M. Mullet, trustee to a point;
- 2. S 30 degrees31'37" W a distance of 27.74 feet through the lands of said David M. Mullet, trustee to a point;
- 3. S 16 degrees26'47" W a distance of 21.97 feet through the lands of said David M. Mullet, trustee to a point;
- 4. S 12 degrees00'06" W a distance of 35.16 feet through the lands of said David M. Mullet, trustee to a point;
- 5. S 18 degrees55'30" W a distance of 117.65 feet through the lands of said David M. Mullet, trustee to a point in the centerline of said road and THERE ENDS.

All iron pins set are 5/8 inch rebars with plastic identification "Galbraith 8703"



Basis of Bearings form Grid North, Ohio State Plane Coordinate System, North Zone, NAD 83 See Holmes County Plat Book <u>19</u> Page <u>4574</u> for survey.

This survey was made and description prepared by Caleb Jerome Galbraith P.S. 8703. on April 23, 2021.

Parcel Number: 1302309001



