

MAP OF SURVEY

NW QUARTER OF SECTION 29
T-14-N; R-13-W
PRAIRIE TOWNSHIP
HOLMES COUNTY, OHIO

202500005239

B: 19 P: 5727
FILED FOR RECORD IN
HOLMES COUNTY, OH
ANITA HALL, COUNTY RECORDER
12/22/2025 03:45 PM
SMALL PLAT . 40.00
PAGES: 1
ORV 294 Pg 3449

N: 365142.409
E: 2115271.931

WAYNE COUNTY

HOLMES COUNTY

30 29

LEGEND

- STONE FOUND
- 5/8" REBAR FOUND (UNLESS NOTED)
- 2" MAG NAIL SET
- 5/8" REBAR SET WITH I.D. CAP MARKED "LINGENFELTER" 8499

REFERENCE SURVEY:
19-0553, 19-2174,
19-2690

BASIS OF BEARING:
THE BEARINGS AS SHOWN
HEREON ARE RELATIVE TO
GRID NORTH OF THE OHIO
STATE PLANE COORDINATE
SYSTEM, NAD 83 (2011)
DATUM

CURVE DATA

A= 282.09'
R= 1120.60'
Δ= 14°25'23"
B= S 12°31'06" E
C= 281.34'

S 19°43'47" E
107.73'

N 19°43'47" W
158.81'

REF. @ 30.00'
N 88°17'36" E 781.98' TOTAL

CURVE DATA

A= 262.05'
R= 1317.70'
Δ= 11°23'40"
B= N 25°25'37" W
C= 261.62'

**12.000
ACRES**

MATTHEW D. SCHUCH
O.R. V-290, P-5225
PPN: 18-00001-000

N 31°07'27" W
214.41'

N 36°36'02" W
232.56'

CURVE DATA

A= 320.71'
R= 740.80'
Δ= 24°48'18"
B= N 49°00'11" W
C= 241.77'

S 03°54'15" W
330.00' TOTAL

REF. @ 30.00'

N 61°24'20" W
119.91'

N 00°18'58" E 2306.29'

SECTION LINE

30 29
30 29



Distances shown hereon are expressed in feet and decimal parts thereof, bearings are used to express angles only, iron pins or monuments were found or set as indicated hereon. All of which I believe to be correct to the best of my knowledge.

By: Jason J. Lingenfelter
JASON J. LINGENFELTER, P.S. #8499
JOB #25-045

11-11-2025
DATE

0' 100' 200' 600'
SCALE: 1" = 200'

APPROVED FOR TRANSFER ONLY

NO SUBDIVISION PLAT REQUIRED

(O.R.C. 711.001 & 711.131)

Lot(s) not for building unless
approved by Board of Health

HOLMES CO. PLANNING COMMISSION

By TS Date 12/22/2025

HCPC

Plat Approved

Holmes County Map Office

12/11/2025 MM

LINGENFELTER SURVEYING

PROFESSIONAL LAND SURVEYING (330)-231-3957