



LINE	ARC	BEARING	DISTANCE	RADIUS	DELTA
A-B		N. 33° 21' 59" W	Chord 150.60'	820.00'	10° 32' 15"
B-C		N. 28° 05' 52" W	69.71'		
C-D		N. 43° 03' 32" W	Chord 134.24'	260.00'	29° 55' 19"
D-E		N. 58° 01' 11" W	47.16'		
E-F		N. 81° 22' 22" W	Chord 206.13'	260.00'	46° 42' 22"
F-G		N. 13° 06' 20" W	240.73'		
G-H		N. 57° 14' 53" E	400.00'		
H-J		N. 27° 40' 46" W	156.50'		
J-K		N. 57° 44' 00" E	145.34'		
K-L		S. 19° 26' 14" E	426.05'		
L-M		S. 84° 07' 47" W	173.77'		
M-N		S. 8° 11' 55" W	99.63'		
N-P		S. 88° 10' 12" E	365.30'		
P-R		S. 0° 45' 17" E	Chord 712.04'	1885.46'	21° 46' 05"
R-S		N. 47° 50' 55" W	Chord 42.83'	185.99'	13° 13' 20"
S-T		N. 41° 14' 15" W	133.49'		
T-U		N. 50° 53' 45" E	80.98'		
U-V		N. 14° 41' 12" E	69.40'		
V-W		N. 39° 06' 15" W	121.00'		
W-Y		S. 50° 53' 45" W	66.00'		
Y-X		S. 39° 06' 15" E	24.00'		
X-A		S. 50° 53' 45" W	75.27'		

NOTE:  
Coordinates refer to the Ohio State Plane Coordinate System (North Zone) to an accuracy of 1:5000 or better.

I hereby certify that this plat is a true delineation showing a 8.06 acre tract of land to be conveyed, prepared from a survey map by P.E. Martin & Associates by Sanford & Schneider, Surveyors along with deed and mortgages.  
Date: Nov. 10, 1976



MAP OFFICE COPY

Received \_\_\_\_\_ 1976  
At \_\_\_\_\_ O'clock \_\_\_\_\_  
Recorded \_\_\_\_\_ 1976  
Holmes County Plat Vol. \_\_\_\_\_ Pg. \_\_\_\_\_  
Fee: \_\_\_\_\_

Holmes County Recorder

HOLMES CO. KNOX TWP. STATE OF OHIO		
TOWN 19N RANGE 15W NE & NW 1/4 SECTION-20		
SCALE: 1" = 200'	APPROVED BY:	DRAWN BY RAS
DATE: Nov. 10, 1976		REVISED
PLAT MADE AT REQUEST OF THE WALLY CORPORATION (FRANCIS SMITH ATTY.)		
SANFORD & SCHNEIDER, SURVEYORS		DRAWING NUMBER
ASHLAND, OHIO		242