

Stone NE cmt  
SW 1/4 SW 1/4  
S6, T8N, R8W

S1°20'03"W  
1293.10'

589°4'37"E 1247.52'

S1°20'3"W  
581.68'

16.695 Ac.  
Vol. 123 Pg. 343

1253.00'

N89°06'37"W  
1757.48'

504.48'

Stone SE cmt  
SW 1/4 SW 1/4  
S6, T8N, R8W

R.S.  
N32°42'0"E  
262.62'

R.S.  
N31°25'0"E  
663.10'

S1°52'26"W 581.75'

220.00'

T.R.29  
N31°25'0"E  
663.10'

SW cmt SW 1/4 SW 1/4  
S6, T8N, R8W

S10, T8N, R9W

T.R.30 (Road Bed)  
N88°43'06"W 462.74'

Stone at  
SE cmt  
S10, T8N, R9W

4.30'  
R.S.  
S17°54'20"W  
415.53' + 4.30' = 419.83'  
T.R.29

I.P.  
262.84'  
R.S.

Stone  
N89°13'0"W  
143.50'

Scale: 1" = 100'

PLAT OF A SURVEY IN  
RICHLAND TWP.  
Known as part of SW 1/4 SW 1/4  
S6, T8N, R8W & SE 1/4 SE 1/4  
S10, T8N, R9W of Richland  
TWP., Holmes Co., Ohio.  
Robert L. Kasner P.S. 5193

